


Aluminum H-Beams

6061-T6 / 25 Foot Lengths


A (Inches)	B (Inches)	t (Inches)	Weight Per Piece (Estimated)	Weight Per Piece (Estimated)
4.000	4.000	0.313	4.844	121.100
5.000	5.000	0.313	6.629	165.720
6.000	5.938	0.250	7.850	196.250
8.000	8.125	0.500	12.990	324.750



Aluminum I-Beams

American Standard 6061-T6 / 25 Foot Lengths

A (Inches)	B (Inches)	t (Inches)	Weight Per Piece (Estimated)	Weight Per Piece (Estimated)
3.000	2.330	0.170	1.994	49.850
3.000	2.509	0.349	2.670	66.750
4.000	2.660	0.190	2.642	66.050
4.000	2.796	0.326	3.373	84.325
5.000	3.000	0.210	3.508	87.700
5.000	3.284	0.494	5.250	131.250
6.000	3.330	0.230	4.390	109.750
6.000	3.443	0.343	5.220	130.500
8.000	4.000	0.270	6.350	158.750
8.000	4.262	0.532	8.810	220.250
10.000	4.660	0.310	8.760	219.000



Aluminum I-Beams

American Standard 6061-T6 / 25 Foot Lengths

A (Inches)	B (Inches)	t (Inches)	Weight Per Piece (Estimated)	Weight Per Piece (Estimated)
3.000	2.330	0.170	1.994	49.850
3.000	2.509	0.349	2.670	66.750
4.000	2.660	0.190	2.642	66.050
4.000	2.796	0.326	3.373	84.325
5.000	3.000	0.210	3.508	87.700
5.000	3.284	0.494	5.250	131.250
6.000	3.330	0.230	4.390	109.750
6.000	3.443	0.343	5.220	130.500
8.000	4.000	0.270	6.350	158.750
8.000	4.262	0.532	8.810	220.250
10.000	4.660	0.310	8.760	219.000