


Steel Angle

A-36 / 20 Foot Lengths

A (Inches)	B (Inches)	t (Inches)	Weight Per Foot (Estimated)	Weight Per Piece (Estimated)
---------------	---------------	---------------	--------------------------------	---------------------------------


1/2	1/2	1/8	.38	7.6
5/8	5/8	1/8	.48	9.6
3/4	3/4	1/8	.59	11.8
7/8	7/8	1/8	.70	14.0
1	5/8	1/8	.64	12.8
1	3/4	1/8	.70	14.0
1	1	1/8	.80	16.0
1	1	3/16	1.16	23.2
1	1	1/4	1.49	29.8
1 1/8	1 1/8	1/8	.90	18.0
1 1/4	1 1/4	1/8	1.01	20.2
1 1/4	1 1/4	3/16	1.48	29.6
1 1/4	1 1/4	1/4	1.92	38.4
1 3/8	7/8	1/8	.91	18.2
1 3/8	7/8	3/16	1.32	26.4
1 1/2	1 1/4	3/16	1.64	32.8
1 1/2	1 1/2	1/8	1.23	24.6
1 1/2	1 1/2	3/16	1.80	36.0
1 1/2	1 1/2	1/4	2.34	46.8
1 1/2	1 1/2	5/16	2.86	57.2
1 1/2	1 1/2	3/8	3.35	67.0
1 3/4	1 1/4	1/8	1.23	24.6
1 3/4	1 1/4	3/16	1.80	36.0
1 3/4	1 1/4	1/4	2.34	46.8
1 3/4	1 3/4	1/8	1.44	28.8
1 3/4	1 3/4	3/16	2.12	42.4
1 3/4	1 3/4	1/4	2.77	55.4



Steel Angle

A-36 / 20 Foot Lengths


A (Inches)	B (Inches)	t (Inches)	Weight Per Foot (Estimated)	Weight Per Piece (Estimated)
2	1 1/4	3/16	1.96	39.2
2	1 1/4	1/4	2.55	51.0
2	1 1/2	1/8	1.44	28.8
2	1 1/2	3/16	2.12	42.4
2	1 1/2	1/4	2.77	55.4
2	2	1/8	1.65	33.0
2	2	3/16	2.44	48.8
2	2	1/4	3.19	63.8
2	2	5/16	3.92	78.4
2	2	3/8	4.70	94.0
2	2	1/2	5.92	118.4
2 1/2	1 1/2	3/16	2.44	48.8
2 1/2	1 1/2	1/4	3.19	63.8
2 1/2	1 1/2	5/16	3.92	78.4
2 1/2	2	3/16	2.75	55.0
2 1/2	2	1/4	3.62	72.4
2 1/2	2	5/16	4.50	90.0
2 1/2	2	3/8	5.30	106.0
2 1/2	2 1/2	3/16	3.07	61.4
2 1/2	2 1/2	1/4	4.10	82.0
2 1/2	2 1/2	5/16	5.00	100.0
2 1/2	2 1/2	3/8	5.90	118.0
2 1/2	2 1/2	1/2	7.70	154.0
3	2	3/16	3.07	61
3	2	1/4	4.1	82
3	2	5/16	5.0	100
3	2	3/8	5.9	118



Steel Angle

A-36 / 20 Foot Lengths


A (Inches)	B (Inches)	t (Inches)	Weight Per Foot (Estimated)	Weight Per Piece (Estimated)
3	2	1/2	7.7	154
3	2 1/2	3/16	3.4	68
3	2 1/2	1/4	4.5	90
3	2 1/2	5/16	5.6	112
3	2 1/2	3/8	6.6	132
3	2 1/2	1/2	8.5	170
3	3	3/16	3.71	74
3	3	1/4	4.9	98
3	3	5/16	6.1	122
3	3	3/8	7.2	144
3	3	1/2	9.4	188
3 1/2	2 1/2	1/4	4.9	98
3 1/2	2 1/2	5/16	6.1	122
3 1/2	2 1/2	3/8	7.2	144
3 1/2	2 1/2	1/2	9.4	188
3 1/2	3	1/4	5.4	108
3 1/2	3	5/16	6.6	132
3 1/2	3	3/8	7.9	158
3 1/2	3	1/2	10.2	204
3 1/2	3 1/2	1/4	5.8	116
3 1/2	3 1/2	5/16	7.2	144
3 1/2	3 1/2	3/8	8.5	170
3 1/2	3 1/2	1/2	11.1	222
4	3	1/4	5.8	116
4	3	5/16	7.2	144
4	3	3/8	8.5	170
4	3	1/2	11.1	222



Steel Angle

A-36 / 20 Foot Lengths


A (Inches)	B (Inches)	t (Inches)	Weight Per Foot (Estimated)	Weight Per Piece (Estimated)
4	3	5/8	13.6	272
4	3 1/2	1/4	6.2	124
4	3 1/2	5/16	7.7	154
4	3 1/2	3/8	9.1	182
4	3 1/2	1/2	11.9	238
4	4	1/4	6.6	132
4	4	5/16	8.6	164
4	4	3/8	9.8	196
4	4	7/16	11.3	226
4	4	1/2	12.8	256
4	4	5/8	15.7	314
4	4	3/4	18.5	370
5	3	1/4	6.6	132
5	3	5/16	8.2	164
5	3	3/8	9.8	196
5	3	1/2	12.8	256
5	3 1/2	1/4	7.0	140
5	3 1/2	5/16	8.7	174
5	3 1/2	3/8	10.4	208
5	3 1/2	1/2	13.6	272
5	3 1/2	5/8	16.8	336
5	3 1/2	3/4	19.8	396
5	5	5/16	10.3	206
5	5	3/8	12.3	246
5	5	1/2	16.2	324
5	5	5/8	20.0	400
5	5	3/4	23.6	472



Steel Angle

A-36 / 20 Foot Lengths

A (Inches)	B (Inches)	t (Inches)	Weight Per Foot (Estimated)	Weight Per Piece (Estimated)
6	3 1/2	1/4	7.9	158
6	3 1/2	5/16	9.8	196
6	3 1/2	3/8	11.7	234
6	3 1/2	1/2	15.3	306
6	4	5/16	10.3	206
6	4	3/8	12.3	246
6	4	1/2	16.2	324
6	4	5/8	20.0	400
6	4	3/4	23.6	472
6	4	7/8	27.2	544
6	6	5/16	12.4	248
6	6	3/8	14.9	298
6	6	1/2	19.6	392
6	6	5/8	24.2	484
6	6	3/4	28.7	574
6	6	1	37.4	748
7	4	3/8	13.6	272
7	4	1/2	17.9	358
7	4	5/8	22.1	442
7	4	3/4	26.2	524
8	4	1/2	19.6	392
8	4	5/8	24.2	484
8	4	3/4	28.7	574
8	6	1/2	23.0	460
8	6	5/8	28.5	570
8	6	3/4	33.8	676
8	6	1	44.2	884



Steel Angle

A-36 / 20 Foot Lengths

A (Inches)	B (Inches)	t (Inches)	Weight Per Foot (Estimated)	Weight Per Piece (Estimated)
8	8	1/2	26.4	528
8	8	5/8	32.7	654
8	8	3/4	38.9	778
8	8	1	51.0	1020
9	4	1/2	21.3	426